IDC Klaassen
CANOR epos IsoTek FINK team GOLDRING Creek Q ACOUSTICS bluehorizon MILTY Stable 33.33 QED
EXCELLENCE IN AUDIO & HIFI – PASSION FOR SOUND – EXPERTISE FOR OVER 50 YEARS

Consumer Price List 2025/1

Please note:

Prices quoted correspond to the non-binding recommended retail price in units/packages/metres and euros including VAT at the applicable rate. Price list, technical characteristics and errors excepted.

Previous CREEK price lists are no longer valid.

IDC Klaassen International
Distribution & Consulting oHG
Am Brambusch 22
44536 Lünen

Phone: +49 (0) 231 22 17 88 22
Fax: +49 (0) 231 99 33 54 99
E-Mail: idc@idc-klaassen.com
Internet: www.idc-klaassen.com

This offer is subject to change. The price list and the prices contained therein are subject to change at any time. We reserve the right to make changes to the product specifications without prior notice in the course of further developments.

4040 Serie

Item No.	EAN Code	RRP €	Model - Colour		Brief description	
CR100110	5060217950333	999,00	4040A Integrated amplifier with DAC and Bluetooth - Black		Output power:	55 W into 8 ohms, 110 W into 4 ohms, both channels driven
					THD:	<0.045%
					Signal-to-noise ratio:	105dBA
					Frequency response:	5Hz to 50 kHz, +/-3dB 10Hz - 20KHz +/-1dB
					Inputs:	2x RCA (unbalanced) and 1x XLR (balanced) - 1x coaxial, 1x optical, 1x USB 2.0 - Bluetooth
					Phono:	retrofittable
CR100111	5060217950340		4040A Integrated amplifier with DAC and Bluetooth - Silver		DAC:	ES9018k2m Sabre DAC
					Headphone output:	6.3mm stereo - 30 - 300 Ohm
					Weight:	2.2kg
					Dimensions:	(W/H/D) 21.5 x 6 x 25.5 cm
CR100120	5060217950357	949,00	4040CD CD Player • Black		Digital outputs:	1x coaxial RCA, 1x optical TOSLINK, 1x AES-EBU balanced digital XLR
					Analogue output:	Stereo RCA
					Current voltage:	100V to 250V, 50/60Hz
					Power consumption:	20W, <0.5W - Max, Standby
					Auto Standby:	Switches off after a preset time without signal.
CR100121	5060217950364		4040CD CD Player • Sillver		Weight:	1.8 KG
					Dimensions:	(W/H/D) 21.5 x 6 x 22 cm

Art.Nr:	EAN Code	UVP €	Modell • Farbe	Kurzbeschreibung

4040A Phono Upgrade & Zubehör

CR100131	5060217950159	169,00	Phono preamplifier retrofitSequel.MK4		Input impedance: 47 kOhm Frequency response: 10 Hz to 20 kHz +/- 0.5 dB Signal-to-noise ratio: >80dB at 40dB gain Distortion factor: <0,005% Max. output power: 10 V RMS Gain : 250dB (316) for high output power MC and low MM Low frequency filter: 100pF or 200pF
CR100132	5060217950371	39,00	EVO Remote control	ONLY FOR EVO SERIES	

Creek amplifiers are designed by Mike Creek and a team of electronics engineers who use the latest CAD technology and advanced testing equipment to create the innovative and clever designs for which Mike Creek is known.

The first Creek amplifier, the CAS4040, launched in 1982 in the UK for an astonishing price of just £99, received overwhelming praise for its sound quality. This success was accompanied by disbelief that a young British Hi-Fi company could compete with established brands and undercut their pricing structures. What the reviewers of the first Creek amplifiers didn't know was that Michael Creek already had extensive experience in the audio industry.



Over the years, Mike Creek has remained true to his fundamental product design philosophy.
The key elements can be summarized as follows:

- Creek stands for a simple, clear design concept,
- characterized by technical sophistication,
- features state-of-the-art electronics,
- designed for people who love music,
- offers minimalist operation,
- always focuses on a holistic system approach.

PREMIUM AUDIO
SOLUTIONS



FOR MORE INFORMATION PLEASE CONTACT

IDC Klaassen International Distribution & Consulting oHG
Am Brambusch 22 • D-44536 Lünen • Germany
E-Mail: idc@idc-klaassen.com | Tel: +49 (0) 231 22 17 88 22
www.idc-klaassen.com

Design and specifications are subject to change without notice, errors excepted.